VELOCE

DAI PRÀ



TECHNICAL DATA

Total height of the machine 1500 mm
Height of the bag breaker 990 mm
Machine width 760mm
Machine length 695mm
Weight 120kg
Pressure 25 bar
Flow rate 0-25 l/min
Granin size max 3 mm
Tank capacity 60 liters
Delivery 1 1/2"'
Motor 50 Hz 400V 1,8 / 2,5 Kw



FUNCTIONING

The machine is suitable for mixing and at the same time injecting and stirring cement grout and/or pre-mixed up to a grain size of 3 mm. The machine is equipped with electrical panel with:

- phase change;
- switched on;
- to close;
- Emergency fungus;
- motion inverter.

The tank with a capacity of 60 liters can be equipped with the following accessories:

- Liter counter;
- Wheel system to move the tank;
- Radio control;

On request it is also possible to have VELOCE also in the pneumatic version

DAI PRÀ SRL
Via A. Vaolta, 37
35010 Villafranca Padovana (fraz. Taggi' di Sopra) - Padova
Tel. +39 049 767973 - Fax +39 049 767192
daipra@daipra.it - www.daipra.it

SPEEDY

DAI PRÀ



FUNCTIONING

With DM-21/11 Speedy it is possible to mix and pump cement mortars with a maximum grain size 3 mm continuously.

Applicatins and areas of use:

Used successfully in civil engineering, slopes, passive and active anchors, self- drilling anchors, micropiles, back filling, tunneling.

The frame is galvanized and guarantee aptimum corrosion protection.

The motor reverse function of Speedy allows unclogging pump body in case of blockage.

Speedy can be loaded from sacks or directly fitted to the silo by means of a plate.

TECHNICAL SPECIFICATION


DESCRIPTION		DESCRIPTION	
Delivery rate	20-39-45-60-lt/min	Loading Height	100 cm
Delivery distance	60 mt	Total Height	115 cm
Delivery pressure	40 bar approx.	Width	70 cm
Electric motor	5.5 kw	Length	160 cm
Electric supply	400 V, 50 Hz	Weight	180 kg
Water pump	1.5 kw	Max grain size	3 mm

STANDARD EQUIPMENT:

- Wather pump
- Mt 22 cable with control button
- Mt 20 grout tube diam.35 mm
- Pressure dischsrage valve
- Standard key case
- Use and maintenance manual
- Spare parts manual
- Automatically polarity control

OPTIONAL:

- Vibrator
- Plate For silo
- Humidity Probe
- Digital water flow meater





MI105 stator MI106 rotor	pressure max	bar	40	Lt/h	1320
MI034 stator MI035 rotor	pressure max	bar	40	Lt/h	2340
MI107 stator MI108 rotor	pressure max	bar	40	Lt/h	2700
MI030 stator MI031 rotor	pressure max	bar	35	Lt/h	3600

DAI PRÀ SRL
VIA A. VAOLTA, 37
35010 VILLAFRANCA PADOVANA (FRAZ. TAGGI' DI SOPRA) - PADOVA
TEL. +39 049 767973 - FAX +39 049 767192
DAIPRA@DAIPRA.IT - WWW.DAIPRA.IT